Wedge

Short Pulse Q-Switched DPSS Laser





Features

Up to 4 mJ Pulse Energy
4 MW Peak Power
400 ps to 2,5 ns Pulsewidth
Single Shot to 100 kHz
266, 355, 532, 1064, 1570, 3100 nm
MOPA configurations
Monolithic Design
Air Cooling
Low heat waste



Applications

Micromachining of glass
Specialty marking
Thin film removal
LIDAR and Bathymetry
Non-linear spectroscopy
Harmonic and parametric generation
Visible to IR OPO pumping
TeraHertz generation












Wedge HB and XB laser models are available at different wavelengths and their main featues are reported in the table below.

All the configurations are based on our proprietary fast active Q-Switch technology, the key point for all the applications requiring high performances in terms of synchronization between the laser and the entire system.

	Wedge models											
	HB 266	HB 355	HB 532	HB 1064	HB 1570	XB 266	XB 355	XB 532	XB 1064	XB 1570	XB 3100	
Primary wavelength	266 nm	355 nm	532 nm	1064 nm	1570 nm	266 nm	355 nm	532 nm	1064 nm	1570 nm	3100 nm	
Max Pulse Energy	150 uJ	200 uJ	1 mJ	2 mJ	400 uJ	500 uJ	600 uJ	2 mJ	4 mJ	0.8 mJ	> 0.1 mJ	
Q-Switch Rep. Rate	Single Shot to 2 kHz						Single Shot to 2 kHz					
Pulsewidth	< 1.5 ns				< 2.5 ns	< 1.5 ns < 2.5 ns					< 3 ns	
Max Peak Power	120 kW	150 kW	800 kW	1.8 MW	200 kW	300 kW	400 kW	1.8 MW	3.6 MW	400 kW	> 30 kW	
Polarization	Linear 100:1 (option: circular polarization)					Linear 100:1 (option: circular polarization)						
Cooling	Air-cooled (option: water cooling and contact cooling)					Air-cooled (option: water cooling and contact cooling)						
DC IN Voltage	Dual 8 V - 15 V					Dual 12 V – 15 V						



OPTIONS AVAILABLE:

Beam expanding and collimation optics
Multi-wavelength configurations
Multimodal Fiber coupling
Low jitter option
Remote control box and software interface
AC-DC power supply

Short Pulse Q-Switched DPSS Laser

Wedge Short Pulse Q-Switched DPSS Laser

Wedge HF and XF are also actively Q-Switched lasers and this feature together with the sub-ns pulsewidth makes these lasers unique on the market. The extremely compact and rugged design coming from airborne applications is very appeciated also in industrial and instrumentation fields.

	Wedge models										
	HF 266	HF 355	HF 532	HF 532 Plus	HF 1064	XF 266	XF 532	XF 532 Plus	XF 1064	XF 1064 Plus	
Primary wavelength	266 nm	355 nm	532 nm	532 nm	1064 nm	266 nm	532 nm	532 nm	1064 nm	1064 nm	
Max Pulse Energy	15 uJ	40 uJ	100 uJ	120 uJ	180 uJ	5 uJ	30 uJ	40 uJ	70 uJ	80 uJ	
Q-Switch Rep. Rate	single shot to 50 kHz	single shot to 100 kHz		20 to 100 kHz	single shot to 100 kHz	single shot to 50 kHz	single shot to 100 kHz	50 to 200 kHz	single shot to 100 kHz	50 to 200 kHz	
Pulsewidth	700 ps to 1.5 ns	500 ps to 1 ns	700 ps to 2.5 ns	500 ps to 2 ns	700 ps to 2.5 ns	400 ps to 700 ps	400 ps to 1.5 ns	400 ps to 1.6 ns	400 ps to 1.5 ns	400 ps to 1.6 ns	
Max Peak Power	20 kW	80 kW	140 kW	200 kW	250 kW	10 kW	75 kW	90 kW	175 kW	150 kW	
Polarization	Linear 100:1 (option: circular polarization)					Linear 100:1 (option: circular polarization)					
Beam quality (M²)	< 1.5					< 1.3					
Cooling	Air-cooled (option: water cooling and contact cooling)					Air-cooled (option: water cooling and contact cooling)					
DC IN Voltage	24 V					24 V					

OPTIONS AVAILABLE:

Beam expanding and collimation optics
Multi-wavelength configurations
Multimodal Fiber coupling
Low jitter option
Remote control box and software interface
AC-DC power supply




Wedge Short Pulse Q-Switched DPSS Laser

In order to better describe the performances of the Wedge models, please refer to the specific datasheets available for each model.

Below you can find the nominal performance curves related to the infrared versions of the Wedge XB 1064nm and of the Wedge HF 1064nm.

Wedge XB 1064nm - PERFORMANCE CURVES





Wedge HF 1064nm - PERFORMANCE CURVES

