






785nm Laser Diode PD 100mw			
Reverse Voltage	$V_r$	2.0	V
Operating Temperature	$T_{op}$	-10 ~ +50	°C
Storage Temperature	$T_{stg}$	-40 ~ +85	°C
Lead soldering temperature (10 sec.)	$T_{is}$	280	°C
<b>Features:</b> <ul style="list-style-type: none"> <li>✗ 785nm</li> <li>✗ Single Mode</li> <li>✗ Built-in PD</li> <li>✗ TO18 package</li> </ul>			
<b>Applications:</b> <ul style="list-style-type: none"> <li>✗ Medical laser treatment</li> <li>✗ Laser indicator</li> <li>✗ Laser detector</li> </ul>			
<b>Specifications</b>			
	Min	Type	Max
Center Wavelength@25°C	775nm	785nm	795nm
Spectral Width (FWHM)	2.0nm		
Output Power	100mw		
Emitter	Single		
Beam Divergence (FWHM)	15° <sub>⊥</sub> x 8° <sub>//</sub>		
Monitor Current	0.5mA		
PD Reverse Voltage	30V		
PD Forward Current	10mA		
Slope Efficiency	1.1mW/mA		
Threshold Current (Typ.)	35mA		
Operating Current (Typ.)	115mA		
Operating Voltage	2.0V		
Package Style	TO18		

**TO18(5.6mm) Package View**



**PIN Bottom View:**



<b>1</b>	<b>LD(-)</b>
<b>2</b>	<b>LD(+)&amp;PD(-)</b>
<b>3</b>	<b>PD(+)</b>

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.

