



515nm~520nm 50mW~60mW 9um Fiber Coupled Diode Laser | Built-in TEC cooler
520nm 50mW |HHL Package| 9um Fiber| Green Diode Laser | Built-in TEC Cooling | High Stability
RWLP-520-050m-9-H8-T

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C
Features: <ul style="list-style-type: none"> ● 520nm ● 9um SM Fiber ● Built-in TEC Cooling ● Built-in Thermistor 			
Applications: <ul style="list-style-type: none"> ● Medical Laser Treatment ● Others 			
Specifications	RWLP-520-050m-9-H8-T		
	Min.	Type	Max.
Center Wavelength@25°C	520nm±10nm		
Spectral Width (FWHM)	----	2nm	----
Output Power	----	50mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	65mA	95mA
Operating Current (Typ.)	----	270mA	290mA
Operating Voltage	----	7.0V	8.0V
Monitor Current	----	----	----
TEC Max Current	1.3A		
TEC Max Voltage	4.0V		
Thermistor	10K		
Fiber Type	SMF-28		
Fiber Core	9um		
Fiber Length	>80cm		
Connector Type	FC/SC/SMA905		
Package Style	8-PIN		

8-Pin Package View:



Pin Out:



PIN	FUNCTION	PIN	FUNCTION
1	RT	5	NC
2	LD (-)	6	NC
3	LD (+)	7	TEC (-)
4	RT	8	TEC (+)

We offer Customized 520nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 2W@520nm+ 10W@980nm)

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.

