


705nm 10mW PM Fiber Coupled Laser Diode with Coaxial Package

700nm~705nm 10mW Coaxial Pigtailed LD with Polarization Maintaining Fiber (SM Fiber)


RWLP-705-010m-PM-PD

705nm Pigtailed Diode Laser		10mW/PM Fiber	
PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	-10~+60	°C
Storage Temperature	T_{stg}	-40~+85	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C
Features: <ul style="list-style-type: none"> ● 705nm ● PM Fiber ● High Reliability ● High Polarization Extinction Ratio 			
Applications: <ul style="list-style-type: none"> ● Biological Instruments ● Analytical Equipment ● Others 			
Specifications	RWLP-705-010m-PM-PD		
	Min	Type	Max
Center Wavelength@25°C	695nm	705nm	715nm
Recommended work Temperature	25°C		
Output Power	----	10mW	----
Fiber Type	Polarization Maintaining Fiber		
Fiber Core	4um		
Polarization Extinction Ratio	13dB	15dB	----
Monitor Current	----	0.3mA	----
Fiber Connector	FC/APC		
Fiber Length	>80cm		
Threshold Current (Typ.)	----	25mA	60mA
Operating Current (Typ.)	----	70mA	80mA
Operating Voltage	----	2.4V	3.0V
Package Style	Coaxial or B82		
High Polarization Extinction Ratio (PER) Version Laser Module is also available, please contact us.			


Coaxial Package View: (Part Number: RWLP-705-010m-PM-PD)



B82 Package View: (Part Number: RWLP-705-010m-PM-B-PD)



PIN Bottom View:



1	LD(-)
2	LD(+)& PD(-)
3	PD(+)

Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

